

VIDEX for GX53 lamp VL-SPF16A-W

INDEX: VL-SPF16A-W

TECHNICAL CARD



Ceiling spotlight luminaire



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



-25° +50°C

Free



INDEX: VL-SPF16A-W

Height	50 mm
Depth	90 mm
In the package	1 pc.
Outer box	50 pcs.
Width	90 mm
Unit nett weight	220g

Signs marking goods

Packaging marking

CE, Utilization



General parameters

IK07

Light source replaceable

WARRANTY 2 YEARS

end user

IP20

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	I

Additional information

Place of installation	Ceiling, Recessed, Flat surface	
Place of application	indoor	
Impact protection	IK07	
Housing colour	White	
Operating temperature range	-25° +50°C	
Mercury content	Does not contain	
Ingress protection	IP20	
Housing material	Aluminum	

Dimensions

EAN

4820246484688




VIDEX for GX53 lamp VL-SPF16A-W

INDEX: VL-SPF16A-W







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



INDEX: VL-SPF16A-W

\bigcirc	Th	e product must be used indoors
	wh in pr	otection against electric shock class I. A product in nich the means of protection against electric shock, addition to the main insulation, is an additional otective circuit connected to the grounding of the wer supply network
Ce	Tł	ne product meets the requirements of EU directives
Ì	ma	s forbidden to throw away waste equipment arked with the symbol of a crossed-out bin with her waste
К07	_	The product withstands a medium impact (e.g., from a blunt object)
"C↓ -25" +50"C	—	Operating temperatures range
Free	_	The product does not contain mercury
IP20	_	Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture