

TECHNICAL CARD



Ceiling spotlight luminaire



VIDEX®



IK07



-25° +50°C



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Input interface Terminal block

Electric shock protection class I

Additional information

Place of installation Ceiling, Recessed, Flat surface

Place of application indoor

Impact protection IK07

Housing colour White

Operating temperature range -25° +50°C

Mercury content Does not contain

Ingress protection IP20

Housing material Aluminum

Dimensions

EAN 4820246484688

VIDEX for GX53 lamp VL-SPF16A-W

INDEX: VL-SPF16A-W

Height 50 mm

Depth 90 mm

Width 90 mm

In the package 1 pc.

Outer box 50 pcs.

Unit nett weight 220g


Signs marking goods

Packaging marking CE, Utilization



VIDEX[®]

VIDEX for GX53 lamp VL-SPF16A-W

INDEX: VL-SPF16A-W

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

INDEX: VL-SPF16A-W



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



IK07

— The product withstands a medium impact (e.g., from a blunt object)



-25° +50°C

— Operating temperatures range



Free

— The product does not contain mercury



IP20

— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture