

TECHNICAL CARD



LED Ambient Floor Light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



360°

ON/OFF
40 000

30 000 h



Free



-20° +40°C



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable	no
--------------------------	----

Type of light source

Dimmable	remote controller
----------	-------------------

Technology	LED
------------	-----

Electrical parameters

Rated voltage, frequency	DC 5 V
--------------------------	--------

Rated current	2 A
---------------	-----

Input interface	USB-A
-----------------	-------

Electric shock protection class	III
---------------------------------	-----

Photometric parameters

Correlated color temperature	RGB + White
------------------------------	-------------

Beam angle	360°
------------	------

On/Off cycles	40000
---------------	-------

Lifetime (L70B50)	30000 h
-------------------	---------

VIDEX VL-TF20-RGB

INDEX: VL-TF20-RGB

Additional information

Place of installation	Floor
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	ABS, PP

Dimensions

EAN	4820246485463
In the package	1 pc.
Outer box	4 pcs.
Height	1515mm
Width	128 mm
Depth	128 mm
Unit nett weight	570g

Signs marking goods

Packaging marking	Recycling of waste, CE, Utilization
-------------------	-------------------------------------

VIDEX®

VIDEX VL-TF20-RGB

INDEX: VL-TF20-RGB

VIDEX[®]

VIDEX VL-TF20-RGB

INDEX: VL-TF20-RGB

INDEX: VL-TF20-RGB



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Rated beam angle



— Rated On/off cycles



— Nominal lifetime (hours)



— The product does not emit ultraviolet light



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture