

VIDEX®

VIDEX-E27-A60-10W-FIL-AMBER-WW

INDEX: VLE-A60FA-10272

TECHNICAL CARD



LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



360°



Ra ≥ 80

ON/OFF
20 000

20 000 h



Not Dimmable



-20° +40°C



No Flicker



No Flicker



CCT 2200K



Free



IP20

WARRANTY 3 YEARS

WARM WHITE



2200K

Warm White / Ciepła biel / Tepla bila / Blanc chaud /
Tepla biela / Warm wit / Meleg feher / Topla bela / Topla
bijela / Warmweiß / Alb cald / Šiltai balta / Silti balta / Soe
valge / Тепло бяла / Bianco caldo.

General parameters

Light source or containing product Light source

Type of light source

Energy class of the light source	F
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
High luminance light source	No
Mains (MLS) or non-mains (NMLS) light source	MLS
Anti-glare shield	No
Technology	LED

VIDEX-E27-A60-10W-FIL-AMBER-WW

INDEX: VLE-A60FA-10272

Electrical parameters

On-mode power (Pon)	10 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	87 mA
Displacement factor (cos φ1)	0.5
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	10

Photometric parameters

Useful luminous flux (Φuse)	1050 Lm
Correlated color temperature	2200K (warm white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	20000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.50
Chromaticity coordinates (y)	0.410
R9 colour rendering index value	>0
The lumen maintenance factor	≥94.8%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (2200K)

VIDEX[®]

VIDEX-E27-A60-10W-FIL-AMBER-WW

INDEX: VLE-A60FA-10272

CRI Min	Ra 80
CRI Max	Ra 88

Additional information

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20

Dimensions

EAN	5904405540015
In the package	1 pc.
Outer box	20 pcs.
Height	105 mm
Width	60 mm
Depth	60 mm
Unit nett weight	32g

Signs marking goods


Packaging marking	Recycling of waste, CE, Not suitable for use under moisture, Utilization
-------------------	--



INDEX: VLE-A60FA-10272

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product must be used indoors



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



Not suitable for use under moisture



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Rated beam angle

360°



— Ra > 80 - color rendering index

Ra > 80



— Rated On/off cycles

ON/OFF
20 000



— Nominal lifetime (hours)

20 000 h



— The product is incompatible with light regulators

Not Dimmable



— Operating temperatures range

-20° +40°C



— The flickering of the light does not exceed the permissible level

No Flicker



— The product has minimal flickering, which should not cause discomfort or danger

No Flicker



— Colour consistency in MacAdam ellipses (SDCM)

<6x
MacAdam
CCT 2200K



— The product does not contain mercury

Free



— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

IP20