

## TECHNISCHE KARTE



WIEDERAUFLADBARE LED-SCHNURWERFER

# VIDEX®



## GARANTIE 2 JAHRE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrallyno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

## Allgemeine Parameter

<b>Betriebsmodus</b>	HIGH, LOW, STROBE, COB, COB + HIGH, RED ON, RED FLASH
<b>Austauschbare Lichtquelle</b>	nein

## Art der Lichtquelle

<b>Dimmbar</b>	nein
<b>Technologie</b>	LED

## Elektrische Parameter

<b>Leistung</b>	5 W + COB
<b>Verbindungsschnittstelle</b>	USB-C

## Photometrische Parameter

<b>Nutzbarer Lichtstrom der enthaltenen Lichtquelle (Φ<sub>use</sub>)</b>	410 Lm
<b>Spitzenlichtintensität</b>	1840 cd

## VIDEX VLF-H035C 410Lm 5000K

### INDEX: VLF-H035C

**Farbtemperatur des Lichts** 5000K (neutralweiß)

### Zusätzliche Information

<b>Farbe des Gehäuses</b>	Schwarz
<b>Fallschutz</b>	1 m
<b>Umgebungstemperaturbereich</b>	-20° +40°C
<b>Batteriespannung</b>	3.7 V
<b>Batterietyp</b>	Li-ion
<b>Batteriekapazität</b>	1800 mAh
<b>Batterieladeanzeige</b>	4 level
<b>Austauschbarer Akku</b>	nein
<b>Quecksilbergehalt</b>	nein
<b>Schutzklasse, IP</b>	IP65
<b>Gehäusematerial</b>	Polycarbonat (PC)

### Maße

<b>Strichcode</b>	4820246481069
<b>Im Paket</b>	1 Stk.
<b>Höhe</b>	46 mm
<b>Menge in der Kiste</b>	20 Stk.
<b>Breite</b>	70 mm
<b>Tiefe</b>	38 mm
<b>Einheit Nettogewicht</b>	108g

### Warenkennzeichnungsschilder

**Verpackungskennzeichnung** CE, Entsorgungsmethode

**VIDEX<sup>®</sup>**

VIDEX VLF-H035C 410Lm 5000K

**INDEX: VLF-H035C**

**VIDEX<sup>®</sup>**

VIDEX VLF-H035C 410Lm 5000K

**INDEX: VLF-H035C**

# VIDEX®

VIDEX VLF-H035C 410Lm 5000K

INDEX: VLF-H035C



VIDEX®  
MODEL | H035C

RECHARGEABLE LED HEADLAMP  
WITH SENSOR



**410**  
MAX LUMENS



1800 mAh  
LI-ION



DUAL  
LIGHT



IP65



1m  
SHOCKPROOF



RED  
LIGHT

VIDEX®  
MODEL | H035C

COB 5W  
5000K

CREE XTE 5W  
5000K



Cree XTE 5W 5000K (Neutral white). Beam angle 80°, distance up to 86 m.  
COB 5W 5000K (Neutral white). Beam angle 120°, distance up to 14 m.

# VIDEX®

VIDEX VLF-H035C 410Lm 5000K

INDEX: VLF-H035C



# VIDEX®

## VIDEX VLF-H035C 410Lm 5000K

### INDEX: VLF-H035C



**INDEX: VLF-H035C**

**VIDEX®** DURABLE SHELL  
MODEL H035C



The body is made of thick polyamide - a hard polymer that protects the device from falls and other difficult environmental conditions.

**VIDEX®** USB-C PORT  
MODEL H035C



Charging port protected from dirt and water by the silicone plug.

**VIDEX®** BATTERY INDICATION  
MODEL H035C



- ● ● ● ● - < 100% charge
- ● ● ● ● - < 80% charge
- ● ● ● ● - < 60% charge
- ● ● ● ● - < 40% charge
- ● ● ● ● - < 20% charge
- ● ● ● ● - < battery discharged

**VIDEX®** NYLON STRAP  
MODEL H035C



Wear-resistant and elastic headband fits comfortably on the head.

# VIDEX®

## VIDEX VLF-H035C 410Lm 5000K

### INDEX: VLF-H035C

**VIDEX®**  
MODEL | H035C

TILT MECHANISM



Adjust the light direction by tilting the headlamp by up to 45 degrees.

---

**VIDEX®**  
MODEL | H035C

PROGRAM ROOT

	Start position	Action A	Result	Action B	Result
	OFF	Press	ON SENSOR**	Hand wave	OFF/ON
	HIGH / LOW / FLASH / RED ON / RED FLASH / COB	Press	SENSOR ON**	Hand wave	OFF/ON*
	OFF	Press and hold for 0.5 sec	Battery status		
	OFF	Press and hold for 3 sec	Lock	Press and hold for 3 sec	Unlock
	OFF	Press	> ON HIGH > LOW > FLASH > RED ON > RED FLASH > OFF >		
	ON/OFF	Press and hold for 0.5 sec	COB ON	Press and hold for 0.5 sec	COB OFF

\*\* Sensor remembers current lighting mode and applies it until the sensor mode will be deactivated.  
 Notes: The modes selection performs within 5 seconds. After this time, the next short press will turn off the light.  
 The headlamp automatically memorizes the last selected lighting mode (except COB mode) and applies it next time when turned on.  
 The Main Light modes and Flood Light (COB) mode can be turned on together unless the sensor is activated.



Technische Änderungen vorbehalten. Die darin enthaltenen Daten Material ist nicht rechtlich bindend.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Polen.



Das Produkt entspricht den Anforderungen der EU-Richtlinien



Es ist verboten, Altgeräte, die mit dem Symbol einer durchgestrichenen Mülltonne gekennzeichnet sind, mit dem Restmüll zu entsorgen



Der Schutz ist bei einem Sturz aus einer Höhe von bis zu 1 Meter wirksam



Not Dimmable

Das Produkt ist nicht kompatibel mit Lichtreglern



-20° +40°C

Betriebstemperaturbereich



Free

Das Produkt enthält kein Quecksilber



IP65

Schutzklasse gegen Staub und Feuchtigkeit. Das Produkt hat vollständigen Schutz gegen Staub und Wasserstrahlen aus allen Richtungen

Datum: 4.06.2026