

## TECHNICAL CARD



LED Headlamp

# VIDEX®



## WARRANTY 2 YEARS

### NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrarno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

### General parameters

<b>Operation mode</b>	HIGH, LOW, MOON, STROBE, RED ON, RED FLASH
<b>Light source replaceable</b>	no

### Type of light source

<b>Dimmable</b>	no
<b>Technology</b>	LED

### Electrical parameters

<b>On-mode power (Pon)</b>	5 W x 2
<b>Input interface</b>	USB-C

### Photometric parameters

<b>Useful luminous flux of the contained light source (Φ<sub>use</sub>)</b>	500 Lm
<b>Peak luminous intensity</b>	3280 cd

## VIDEX VLF-H055D 500Lm 5000K

### INDEX: VLF-H055D

<b>Correlated color temperature</b>	5000K (neutral white)
<b>Additional information</b>	
<b>Housing colour</b>	Black
<b>Fall protection</b>	1 m
<b>Operating temperature range</b>	-20° +40°C
<b>Battery voltage</b>	3.7 V, 1.5 V
<b>Battery type</b>	Li-ion VLF-B12, AAA disposable battery
<b>Battery capacity</b>	1200 mAh
<b>Battery indicator</b>	4 level
<b>Battery replaceable</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP65
<b>Housing material</b>	PC

### Dimensions

<b>EAN</b>	4820246483100
<b>In the package</b>	1 pc.
<b>Height</b>	45 mm
<b>Outer box</b>	20 pcs.
<b>Width</b>	60 mm
<b>Depth</b>	48 mm
<b>Unit nett weight</b>	72g

# VIDEX®

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D

## Signs marking goods

Packaging marking

CE, Utilization



# VIDEX®

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D



# VIDEX®

## VIDEX VLF-H055D 500Lm 5000K

### INDEX: VLF-H055D

not legally binding.

Allegró opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



1m  
SHOCK  
RESISTANT

— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP65

— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions