

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 2 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	HIGH, LOW, MOON, STROBE, RED ON, RED FLASH
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	5 W x 2
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	500 Lm
--	--------

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	3280 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V, 1.5 V
Battery type	Li-ion VLF-B12, AAA disposable battery
Battery capacity	1200 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

Dimensions

EAN	4820246483100
In the package	1 pc.
Height	45 mm
Outer box	20 pcs.
Width	60 mm
Depth	48 mm
Unit nett weight	72g

VIDEX®

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D**Signs marking goods****Packaging marking**

CE, Utilization



VIDEX®

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D



VIDEX®

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D

not legally binding.

Allegró opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



1m
SHOCK
RESISTANT

— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP65

— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions