

INDEX: VLF-H056

TECHNICAL CARD



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



VIDEX VLF-H056 1400Lm 6500K

INDEX: VLF-H056

1m	\square	°c⋒≘	
	$\langle \otimes \rangle$	5	
SHOCK RESISTANT	Not Dimmable	-20° +40°C	

Free IP65

WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / KaltweiB / Alb rece / Šalta balta / Auksti balta / Kűlm valge.

General parameters

Operation mode	HIGH, LOW, STROBE, RED ON, RED FLASH	
Light source replaceable	no	
Battery Warranty 1 year		

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	1400 Lm
Peak luminous intensity	6480 cd

Correlated color tomporature	6500K (cold
Correlated color temperature	white)

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650 (2pcs)
Battery voltage	3.7 V
Battery capacity	2200 mAh (2pcs)
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

Dimensions

EAN 482024648		
Height	48 mm	
Depth	32 mm	
In the package	1 pc.	
Outer box	20 pcs.	
Width	65 mm	
Unit nett weight	171g	

Signs marking goods

Packaging marking



VIDEX VLF-H056 1400Lm 6500K

INDEX: VLF-H056













INDEX: VLF-H056







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

Ce	Th	e product meets the requirements of EU directives
R		s forbidden to throw away waste equipment marked with the symbol of a ssed-out bin with other waste
SHOCK RESISTANT	_	The protection is effective in case of a fall from a height of up to 1 meter
Not Dimmable	-	The product is incompatible with light regulators
'C	—	Operating temperatures range
Free	_	The product does not contain mercury
000 1965	_	Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions