

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 3 YEARS

General parameters

| | |
|---------------------------------|---|
| Operation mode | RED HIGH, RED MIDDLE, RED LOW, RED FLASH, GREEN HIGH, GREEN MIDDLE, GREEN LOW, GREEN FLASH, FLOOD HIGH, FLOOD MIDDLE, FLOOD LOW, SPOT HIGH, SPOT MIDDLE, SPOT LOW, SPOT TURBO, FLOOD TURBO |
| Light source replaceable | no |
| Battery Warranty | 1 year |

Type of light source

| | |
|-------------------|-----|
| Dimmable | yes |
| Technology | LED |

Electrical parameters

| | |
|------------------------|-------|
| Input interface | USB-C |
|------------------------|-------|

Photometric parameters

| | |
|---|---------|
| Useful luminous flux of the contained light source (Φ_{use}) | 1700 Lm |
|---|---------|

VIDEX VLF-H057 1700Lm 5000K

INDEX: VLF-H057

| | |
|-------------------------------------|---|
| Peak luminous intensity | 20566 cd |
| Correlated color temperature | 5000K (neutral white), Red, Green |

Additional information

| | |
|------------------------------------|------------------------|
| Housing colour | Black |
| Fall protection | 1 m |
| Operating temperature range | -20° +40°C |
| Battery voltage | 3.7 V |
| Battery type | Li-ion 18650 (2pcs) |
| Battery capacity | 2200 mAh (2pcs) |
| Battery indicator | 5 level |
| Battery replaceable | yes |
| Mercury content | Does not contain |
| Ingress protection | IP65 |
| Housing material | Polyamide |

Dimensions

| | |
|-------------------------|---------------|
| EAN | 4823135400189 |
| In the package | 1 pc. |
| Height | 48 mm |
| Outer box | 20 pcs. |
| Width | 65 mm |
| Depth | 36.5 mm |
| Unit nett weight | 198g |

INDEX: VLF-H057

Signs marking goods

Packaging marking

CE, Utilization



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



Dimmable

— The product supports brightness adjustment



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP65

— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions