

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, RED ON, RED FLASH, FLOOD HIGH, FLOOD LOW
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	600 Lm
---	--------

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	10800 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-pol
Battery capacity	1800 mAh
Battery indicator	4 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP55
Housing material	Polyamide

Dimensions

EAN	4820246486811
In the package	1 pc.
Height	80 mm
Outer box	20 pcs.
Width	49 mm
Depth	39 mm
Unit nett weight	125g

Signs marking goods

VIDEX[®]

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189**Packaging marking**

CE, Utilization



VIDEX®

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189



VIDEX®

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189



VIDEX[®]

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189

VIDEX®

VIDEX VLF-H189 600Lm 5000K

INDEX: VLF-H189



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



1m
SHOCK
RESISTANT

— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury