

TECHNICAL CARD



LED Light for Magnetic slim track light system




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®

VIDEX VL-TRMS-LD19B Black

INDEX: VL-TRMS-LD19B



WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product	Light source
------------------------------------	--------------

Light source replaceable	no
--------------------------	----

Type of light source

Energy class of the light source	G
----------------------------------	---

Dimmable	no
----------	----

Directional (DLS) or non-directional (NDLS) light source	DLS
--	-----

Connected light source (cls)	no
------------------------------	----

Color-tunable light source	no
----------------------------	----

Mains (MLS) or non-mains (NMLS) light source	NMLS
--	------

High luminance light source	No
-----------------------------	----

Anti-glare shield	No
Technology	LED

Electrical parameters

On-mode power (Pon)	18 W
---------------------	------

Rated voltage, frequency	DC 48 V
--------------------------	---------

Rated current	375 mA
---------------	--------

Input interface	2 Wires Busbar
-----------------	-------------------

Electric shock protection class	III
---------------------------------	-----

Displacement factor (cos φ1)	0.9
------------------------------	-----

Survival factor	1
-----------------	---

Energy consumption in on-mode of the light source (kWh/1000h)	18
---	----

Photometric parameters

Useful luminous flux (Φuse)	1400 Lm
-----------------------------	---------

Correlated color temperature	4000K (neutral white)
------------------------------	--------------------------

Beam angle	90°
------------	-----

Color rendering index (CRI)	Ra > 90
-----------------------------	---------

On/Off cycles	20000
---------------	-------

Lifetime (L70B50)	30000 h
-------------------	---------

Useful luminous flux of the light source reference	in a wide cone (120°)
--	-----------------------

Chromaticity coordinates (x)	0.38
------------------------------	------

Chromaticity coordinates (y)	0.38
------------------------------	------

R9 colour rendering index value	>0
---------------------------------	----

The lumen maintenance factor	≥96%
------------------------------	------

INDEX: VL-TRMS-LD19B

Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)
CRI Min	Ra 90
CRI Max	Ra 95

Unit nett weight 215g

Signs marking goods

Packaging marking

Recycling of
waste, CE,
Utilization

Additional information

Place of installation	Busbar for magnetic slim track
Place of application	indoor
Housing colour	Black
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-20° +45°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum alloy, Acrylic

Dimensions

EAN	4820246485753
In the package	1 pc.
Outer box	30 pcs.
Height	26 mm
Width	352 mm
Depth	24 mm




VIDEX[®]

VIDEX VL-TRMS-LD19B Black



















INDEX: VL-TRMS-LD19B

INDEX: VL-TRMS-LD19B



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

-  The product must be used indoors
-  Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels
-  Minimum distance from the illuminated object
-  Waste recycling after the end of the product's service life
-  The product meets the requirements of EU directives
-  It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
-  — Rated beam angle
-  — Ra > 90 - color rendering index
-  — Rated On/off cycles
-  — Nominal lifetime (hours)
-  — The product does not emit ultraviolet light
-  — The product is incompatible with light regulators
-  — Operating temperatures range
-  — The flickering of the light does not exceed the permissible level
-  — The product has minimal flickering, which should not cause discomfort or danger
-  — Colour consistency in MacAdam ellipses (SDCM)
-  — The product does not contain mercury
-  — Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture