

VIDEX®

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrarno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	1500 Lm
-----------------------------------------------------------------------------	---------

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	12000 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	4000 mAh
Battery type	Li-ion 21700
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP67
Housing material	Anodized aluminum

Dimensions

EAN	4820246484992
In the package	1 pc.
Height	140 mm
Outer box	20 pcs.
Width	30 mm
Depth	30 mm
Unit nett weight	87g

VIDEX[®]

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z**Signs marking goods****Packaging marking**

CE, Utilization



VIDEX®

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z

VIDEX[®]

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z

VIDEX®

VIDEX VLF-A231Z 1500Lm 5000K

INDEX: VLF-A231Z



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegró opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Kraków, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product is incompatible with light regulators

— Operating temperatures range

— The product does not contain mercury

— Class of protection against dust and moisture. The product has full protection against dust and short-term immersion in water up to a depth of 1 meter

Date: 4.06.2026