

TECHNICAL CARD



LED RECHARGEABLE READING LAMP



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



Ra ≥ 80



Free



Dimmable



-20° +40°C



Free



IP20

WARRANTY 2 YEARS

General parameters

| | |
|--------------------------|----|
| Light source replaceable | no |
|--------------------------|----|

Type of light source

| | |
|----------|-----|
| Dimmable | yes |
|----------|-----|

| | |
|------------|-----|
| Technology | LED |
|------------|-----|

Electrical parameters

| | |
|---------------------|-------|
| On-mode power (Pon) | 0.7 W |
|---------------------|-------|

| | |
|-----------------|-------|
| Input interface | USB-C |
|-----------------|-------|

| | |
|---------------------------------|-----|
| Electric shock protection class | III |
|---------------------------------|-----|

Photometric parameters

| | |
|---------------|-------|
| Luminous flux | 60 Lm |
|---------------|-------|

| | |
|------------------------------|---|
| Correlated color temperature | 6500K (cold white), 4000K (neutral white), 3000K (warm white) |
|------------------------------|---|

| | |
|-----------------------------|---------|
| Color rendering index (CRI) | Ra > 80 |
|-----------------------------|---------|

| | |
|---------|-------|
| CRI Min | Ra 80 |
|---------|-------|

VIDEX VL-NL134W White

INDEX: VL-NL134W

| | |
|---------|-------|
| CRI Max | Ra 88 |
|---------|-------|

Additional information

| | |
|----------------------|--------|
| Place of application | indoor |
|----------------------|--------|

| | |
|----------------|-------|
| Housing colour | White |
|----------------|-------|

| | |
|-----------------------|----|
| Ultraviolet radiation | no |
|-----------------------|----|

| | |
|---------------|----|
| Motion sensor | no |
|---------------|----|

| | |
|-----------------------------|------------|
| Operating temperature range | -20° +40°C |
|-----------------------------|------------|

| | |
|-----------------|-------|
| Battery voltage | 3.7 V |
|-----------------|-------|

| | |
|--------------|--------|
| Battery type | Li-pol |
|--------------|--------|

| | |
|------------------|----------|
| Battery capacity | 1000 mAh |
|------------------|----------|

| | |
|---------------------|----|
| Battery replaceable | no |
|---------------------|----|

| | |
|-----------------|------------------|
| Mercury content | Does not contain |
|-----------------|------------------|

| | |
|--------------------|------|
| Ingress protection | IP20 |
|--------------------|------|

| | |
|------------------|-----|
| Housing material | ABS |
|------------------|-----|

Dimensions

| | |
|-----|---------------|
| EAN | 4823135400486 |
|-----|---------------|

| | |
|----------------|-------|
| In the package | 1 pc. |
|----------------|-------|

| | |
|--------|--------|
| Height | 290 mm |
|--------|--------|

| | |
|-----------|---------|
| Outer box | 96 pcs. |
|-----------|---------|

| | |
|-------|-------|
| Width | 85 mm |
|-------|-------|

| | |
|-------|-------|
| Depth | 30 mm |
|-------|-------|

| | |
|------------------|-----|
| Unit nett weight | 76g |
|------------------|-----|

Signs marking goods

| | |
|-------------------|-----------------|
| Packaging marking | CE, Utilization |
|-------------------|-----------------|

INDEX: VL-NL134W

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegra opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 80

— Ra > 80 - color rendering index



Free

— The product does not emit ultraviolet light



Dimmable

— The product supports brightness adjustment



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP20

— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture