

INDEX: VLE-SLSO-305

TECHNICAL CARD



LED Solar Street light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



INDEX: VLE-SLSO-305

Correlated color temperature	5000K (neutral white)		
Beam angle	90 × 130°		
Color rendering index (CRI)	Ra > 80		
On/Off cycles	20000		
Lifetime	30000 h		
Chromaticity coordinates (x)	0.34		
Chromaticity coordinates (y) 0.359			

Additional information

Battery power	80 Wh
Place of installation	Pillar
Place of application	outdoor
Impact protection	IK07
Housing colour	Gray
Minimum distance from the illuminated object	0.5 м
Diffuser material	Polycarbonate (PC)
Motion sensor	no
Operating temperature range	-20° +50°C
Battery type	LiFePO4
Battery voltage	3.2 V
Battery capacity	25000 mAh
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Aluminum alloy

WARRANTY 2 YEARS

Not Dimmable -20°C +50°C

Ra ≥ 80

C

90×130°



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

0N/0FF 20 000

Free

IK07

IP65

30 000 h

General parameters

Light source replaceable	no
Type of light source	
Dimmable	no
Technology	LED

Electrical parameters

Cable length	1 m
Electric shock protection class	
Displacement factor (cos φ1)	-

Photometric parameters

Luminous flux 2500 Lm	



INDEX: VLE-SLSO-305

Dimensions

EAN	5904405541203
Height	495 mm
Depth	54 mm
Width	210 mm
In the package	1 pc.
Outer box	4 pcs.



Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization







INDEX: VLE-SLSO-305










INDEX: VLE-SLSO-305




STREET LIGHT









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

씁	Th	e product must be used outdoors
0 ₿	Mir	nimum distance from the illuminated object
	su	ass III protection against electric shock - ensured by pplying a specific product with a safe very low voltage ELV) without the risk of creating a voltage above safe levels
Ċ	Wa	aste recycling after the end of the product's service life
CE	Th	e product meets the requirements of EU directives
R		s forbidden to throw away waste equipment marked with e symbol of a crossed-out bin with other waste
90×130°	_	Effective light beam angle
Ra ≥ 80		Ra > 80 - color rendering index
ON/OFF 20 000	_	Rated On/off cycles
1K07		The product withstands a medium impact (e.g., from a blunt object)
000 h	_	Nominal lifetime (hours)
Not Dimmable	_	The product is incompatible with light regulators
°C↓ -20°C +50°C	_	Operating temperatures range
Free	_	The product does not contain mercury
IP65	_	Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions