

## TECHNICAL CARD



Mini LED Flashlight

# VIDEX®



## WARRANTY 2 YEARS

### General parameters

Operation mode	HIGH, MIDDLE, LOW, RED ON, UV
Light source replaceable	no

### Type of light source

Dimmable	no
Technology	LED

### Electrical parameters

Input interface	USB-C
-----------------	-------

### Photometric parameters

Useful luminous flux of the contained light source ( $\Phi_{use}$ )	400 Lm
Correlated color temperature	5000K (neutral white), Red, UV
Peak luminous intensity	4650 cd

### Additional information

Housing colour	Gray
----------------	------

## VIDEX VLF-AK012 400Lm 5000K

### INDEX: VLF-AK012

Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	250 mAh
Battery type	Li-pol
Battery indicator	4 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Aluminum

### Dimensions

EAN	4820246488129
In the package	1 pc.
Outer box	80 pcs.
Height	64 mm
Width	17 mm
Depth	17 mm
Unit nett weight	15g

### Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------



**VIDEX<sup>®</sup>**

VIDEX VLF-AK012 400Lm 5000K

**INDEX: VLF-AK012**

# VIDEX®

## VIDEX VLF-AK012 400Lm 5000K

### INDEX: VLF-AK012



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 4.06.2026