

## TECHNICAL CARD



Tactical LED Flashlight

# VIDEX®



## WARRANTY 3 YEARS

### General parameters

<b>Operation mode</b>	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE, RED HIGH, RED MIDDLE, RED LOW, GREEN HIGH, GREEN MIDDLE, GREEN LOW
<b>Light source replaceable</b>	no
<b>Battery Warranty</b>	1 year

### Type of light source

<b>Dimmable</b>	no
<b>Technology</b>	LED

### Electrical parameters

<b>On-mode power (Pon)</b>	20 W
<b>Input interface</b>	USB-C

### Photometric parameters

<b>Useful luminous flux of the contained light source (Φ<sub>use</sub>)</b>	2000 Lm
<b>Correlated color temperature</b>	5000K (neutral white), Red, Green

## VIDEX VLF-AT255RG 2000Lm 5000K

### INDEX: VLF-AT255RG

<b>Peak luminous intensity</b>	77600 cd
--------------------------------	----------

### Additional information

<b>Housing colour</b>	Black
<b>Fall protection</b>	2 m
<b>Operating temperature range</b>	-20° +40°C
<b>Battery voltage</b>	3.7 V
<b>Battery capacity</b>	4000 mAh
<b>Battery type</b>	Li-ion 21700, Li-ion 18650
<b>Battery indicator</b>	5 level
<b>Battery replaceable</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP68
<b>Housing material</b>	Heavy-anodized aircraft aluminum

### Dimensions

<b>EAN</b>	4820246483704
<b>In the package</b>	1 pc.
<b>Height</b>	150 mm
<b>Outer box</b>	20 pcs.
<b>Width</b>	40 mm
<b>Depth</b>	31 mm
<b>Unit nett weight</b>	159g

### Signs marking goods

<b>Packaging marking</b>	CE, Utilization
--------------------------	-----------------

**VIDEX<sup>®</sup>**

VIDEX VLF-AT255RG 2000Lm 5000K

**INDEX: VLF-AT255RG**

**VIDEX<sup>®</sup>**

VIDEX VLF-AT255RG 2000Lm 5000K

**INDEX: VLF-AT255RG**

**VIDEX®**

VIDEX VLF-AT255RG 2000Lm 5000K

**INDEX: VLF-AT255RG**

# VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



**VIDEX®**

VIDEX VLF-AT255RG 2000Lm 5000K

**INDEX: VLF-AT255RG**

# VIDEX®

## VIDEX VLF-AT255RG 2000Lm 5000K

### INDEX: VLF-AT255RG



Mode	Initial State	Action A	Result	Action B	Result
WHITE	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> TURBO > HIGH > MIDDLE > LOW > MOON >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit
GREEN	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> HIGH > MIDDLE > LOW >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit
RED	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> HIGH > MIDDLE > LOW >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegra opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

## INDEX: VLF-AT255RG



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture.  
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter