

VIDEX®

VLF-H075C



550

MAXI LUMENS

ON/OFF
SENSOR

TECHNICAL PARAMETERS ТЕХНІЧНІ ПАРАМЕТРИ PARAMETRY TECHNICZNE

	HIGH*	LOW	COB HIGH	COB LOW	COB+HIGH*	RED ON	RED FLASH	
1	500Lm	140Lm	120Lm	45Lm	550Lm	4.5Lm	4.5Lm	
2	2h 20min	6h	3h 30min	9h	2h	17h	30h	
3	130m	70m	10m	5m	130m	-	-	
4	4000cd	1000cd	24cd	10cd	4000cd	-	-	
5	5000 K							
6	CREE XPG3 5W, COB 3W							
7	Li-Polymer VLF-B12 1200 mAh 3.7 V / 3x AAA							
8	Type-C, 5V 0.8A							
9	2.5 h							
10	IP65							
11	1.5 m							
12	65x45x50 mm							
13	60 g							

*The High and COB+High modes runtime is measured under enabled overheat protection system of the device, which also reduces levels of Output, Distance, and Intensity.

MAIN FEATURES

- High maximum output 550 lumens.
- Built-in motion sensor
- Works with Li-Polymer battery and AAA batteries
- High brightness red light.
- Light weight.

INCLUDED

- Headlamp VLF-H075C;
- Head band;
- Li-Ion rechargeable battery Videx VLF-B12 1200mAh;
- Videx alkaline battery AAA 3pcs;
- Charging cable;
- User's manual.

LIGHTING MODES

- High** - main light maximum brightness
- Low** - main light minimum brightness
- COB High** - secondary light maximum brightness
- COB Low** - secondary light minimum brightness
- COB+High** - total maximum brightness

- Red on** - red continuous light
- Red flash** - red flashing light

OPERATING INSTRUCTION

Button - turns the light on and off and switches between modes. Short press **Button** - turn on the light and switch between modes cyclically.

Long press (0.5 seconds) **Button** with the light switched on - remember current mode and switch the light off. Short press again - turn on the last remembered mode.

Button - activates sensor that allows you to turn on/off the light using gestures, displays the current battery level.


Short press **Button** with the light switched on - remember current mode and later switch on/off by the sensor. A blue light between buttons indicates that the sensor is activated. After that, you can turn on/off the last selected mode with a wave of your hand at a close distance from the device.

Short press **Button** with the light switched off - turn on HIGH mode and switch on/off by sensor.

BATTERY STATUS INDICATION

With the light switched off, press and hold the **Button** for 0.5 seconds to see the battery status. The indication will last for 3 seconds. The battery status is also continuously displayed when the light is turned on.

5 divisions - <100% charge;



- 4 divisions - <80% charge;
- 3 divisions - <60% charge;
- 2 divisions - <40% charge;
- 1 division - <20% charge;
- 1 division flashes - battery discharged.

CHARGING

ATTENTION! Only VLF-B12 3.7V lithium-polymer battery can be charged. AAA batteries cannot be charged. Plug the USB-A socket of the charging cable into electrical outlet. Switch off the light, open the protective cover and connect the charging cable to the headlamp port.


When charging, the indicator flashes. When fully charged, all 5 divisions of the indicator glow constantly.

After a full charge, unplug the charging cable and close the protective cover to prevent water and dust from entering the headlamp body.

© The original batteries are supplied charged and can be used immediately after purchase, however it is recommended that the rechargeable battery be fully charged before first use. The battery needs to be charged in time before it is completely discharged. During long periods of storage, it is recommended to keep the battery charging level at about half capacity to extend its life time.

BATTERY REPLACEMENT

- a) Fully open the mechanism for adjusting the angle of the lantern;



- b) Pull up the lock located behind the control buttons and open the back cover;
- c) Insert the battery/s according to the diagram shown on the inside of the battery compartment;
- d) Close the cover until it snaps and test the headlamp.

MAINTENANCE AND SAFETY INSTRUCTIONS

- For long-term storage, it is necessary to remove the batteries from the headlamp to avoid leakage.
- It is recommended to keep the battery contacts clean to maintain the original performance.
- ATTENTION.** Avoid direct light into eyes as it may cause the eyes damage.
- Do not charge AAA batteries. It may cause into leakage and damage the device.
- Do not use batteries other than those specified in the technical specifications.
- Do not disassemble the sealed body of the headlamp as this may compromise performance and void the warranty.
- Keep out of the reach of children.

WARRANTY

The warranty for the headlamp is 2 years, for the VLF-B12 battery - 1 year. The warranty does not cover accessories. The LED source inside the headlamp is not replaceable. If the LED fails, the whole headlamp



WWW.VIDEX.UA



WWW.VIDEX.COM.PL

Виробник: ПП «Аллегро-опт», вул. Героїв Маріуполя, 106-Ж, м. Кропивницький, Україна, 25004. Тел./факс: +38(0522)245377. Вироблено на виробничих потужностях: Нінхай Ісен Дейлі Юз Ко ЛТД. Адреса: Сідан Таун, Нінхай, Нінбо, Чжецзян, Китай.

Щодо прийняття претензій звертається до Виробника. Дата виготовлення і номер партії зазначені на виробі та на упаковці.

Producer/Producent: Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland. Made in P.R.C.



should be replaced. During the warranty period, a faulty headlamp can be exchanged or returned subject to the following conditions:

- The instructions for use in this manual have been followed;
- There are no signs of deep mechanical damage on the product;
- A receipt and accessories have been saved.

ENVIRONMENTAL PROTECTION

Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

The producer shall not be responsible for any damage resulting from the failure to follow above instructions. The producer reserves the right to make updates of this user's manual.

! Note: Output, Runtime, Distance, Intensity and Charging time results have been tested with a stock battery VLF-B12 1200 mAh 3.7V. The above mentioned parameters may vary between environments.

