

TECHNICAL CARD



Spot track luminaire



VIDEX®



IK07



-20° +40°C



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Input interface 2 Wires
Busbar

Electric shock protection class I

Additional information

Place of installation Busbar track

Place of application indoor

Impact protection IK07

Housing colour Black

Operating temperature range -20° +40°C

Mercury content Does not contain

Ingress protection IP20

Housing material Aluminum

Dimensions

EAN 4820246482141

Height 100 mm

VIDEX-GU10-SKOT-BLACK

INDEX: VL-SPF05C-B


Outer box 20 pcs.

Width 55 mm

Depth 55 mm



INDEX: VL-SPF05C-B



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



IK07

— The product withstands a medium impact (e.g., from a blunt object)



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP20

— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture