

TECHNICAL CARD



Spot track luminaire



VIDEX®



IK07



-20° +40°C



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Input interface 2 Wires
Busbar

Electric shock protection class I

Additional information

Place of installation Busbar track

Place of application indoor

Impact protection IK07

Housing colour Black

Operating temperature range -20° +40°C

Mercury content Does not contain

Ingress protection IP20

Housing material Aluminum

Dimensions

EAN 4820246482141

Height 100 mm

VIDEX-GU10-SKOT-BLACK

INDEX: VL-SPF05C-B


Outer box 20 pcs.

Width 55 mm

Depth 55 mm



INDEX: VL-SPF05C-B



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



— The product withstands a medium impact (e.g., from a blunt object)



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture