



INDEX: VL-SPF12A-W

TECHNICAL CARD









Ceiling spotlight luminaire VL-SPF12A-W

INDEX: VL-SPF12A-W









Outer box	40 pcs.
Width	80 mm
Depth	80 mm

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	1

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	White
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions

EAN	4820246483018
Height	84 mm








Ceiling spotlight luminaire VL-SPF12A-W

INDEX: VL-SPF12A-W





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



- The product withstands a medium impact (e.g., from a blunt object)



- Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 21.11.2025