



INDEX: VL-SPF14A-B

TECHNICAL CARD









Ceiling spotlight luminaire VL-SPF14A-B

INDEX: VL-SPF14A-B









Depth	90 mm
Outer box	20 pcs.
Width	90 mm

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	ı

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions

EAN	4820246482912
Height	140 mm








Ceiling spotlight luminaire VL-SPF14A-B

INDEX: VL-SPF14A-B





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product withstands a medium impact (e.g., from a blunt object)



- Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 23.07.2025