

INDEX: VL-SPF20B-B

TECHNICAL CARD



Ceiling spotlight luminaire

















WARRANTY 2 YEARS

General parameters

Light source replaceable	end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	ı

Additional information

Place of installation	Ceiling
Place of application	indoor
Housing colour	Black
Impact protection	IK07
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy

Dimensions

EAN 4820246484732

VIDEX for 3xGX53 lamp VL-SPF20B-B

INDEX: VL-SPF20B-B

Height	45 mm, 30 mm
Width	80 mm, 200 mm
Depth	150 mm, 80 mm
Outer box	5 pcs.
Unit nett weight	1kg
In the package	1 pc.

Signs marking goods

Packaging marking	CE, Utilization
	0_, 00






VIDEX for 3xGX53 lamp VL-SPF20B-B

INDEX: VL-SPF20B-B







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

Date: 21.11.2024