

**INDEX: VL-SPF20B-W** 

# **TECHNICAL CARD**



Ceiling spotlight luminaire

















## **WARRANTY 2 YEARS**

# **General parameters**

end user

# **Electrical parameters**

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	ı

### **Additional information**

Place of installation	Ceiling	
Place of application	indoor	
Impact protection	IK07	
Housing colour	White	
Operating temperature range	-25° +50°C	
Mercury content	Does not contain	
Ingress protection	IP20	
Housing material	Aluminum, Iron alloy	

### **Dimensions**

	EAN	4820246484749
	EAN	4820246484749
<b>EAN</b> 4820246484749		

# VIDEX for 3xGX53 lamp VL-SPF20B-W

## **INDEX: VL-SPF20B-W**

Height	45 mm, 30 mm	
Depth	150 mm, 80 mm	
In the package	1 pc.	
Outer box	5 pcs.	
Width	80 mm, 200 mm	
Unit nett weight	1kg	

# Signs marking goods

<b>Packaging</b>	marking	CE,	Utilization






## VIDEX for 3xGX53 lamp VL-SPF20B-W

### **INDEX: VL-SPF20B-W**







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 30.08.2025