

INDEX: VL-SPF21B-BP

TECHNICAL CARD



Ceiling spotlight luminaire











VIDEX for 6xGX53 lamp VL-SPF21B-BP

INDEX: VL-SPF21B-BP









WARRANTY 2 YEARS

General p	parameters
-----------	------------

Light source replaceable end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	I

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy, PC, Ceramics

Dimensions

EAN	4820246487092
EAN	4820246487092

Height	70 mm, 36 mm
Depth	150 mm, 85 mm
In the package	1 pc.
Outer box	5 pcs.
Width	85 mm, 280 mm
Unit nett weight	1.03kg

Signs marking goods

Packaging marking CE, Utilization






VIDEX for 6xGX53 lamp VL-SPF21B-BP

INDEX: VL-SPF21B-BP







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.
Protection against solid objects larger than 12 mm; no protection against moisture

Date: 1.08.2025