

**INDEX: VL-SPF22B-B** 

# **TECHNICAL CARD**



Ceiling spotlight luminaire











## VIDEX for 8xGX53 lamp VL-SPF22B-B

#### INDEX: VL-SPF22B-B









7	泛	<	\
	IKO	7	



## **General parameters**

end user

## **Electrical parameters**

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	ı

#### **Additional information**

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy

#### **Dimensions**

Height	45 mm, 30 mm
Depth	80 mm, 200 mm, 400 mm
In the package	1 pc.
Outer box	5 pcs.
Width	220 mm, 80 mm

## Signs marking goods

marking	CE, Utilization
•	
	marking






### VIDEX for 8xGX53 lamp VL-SPF22B-B

#### **INDEX: VL-SPF22B-B**







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives  $% \left( \mathbf{r}^{\prime }\right) =\left( \mathbf{r}^{\prime }\right)$ 



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



- Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 28.07.2025