

VIDEX for 6xGX53 lamp with backlight VL-SPF22B-

INDEX: VL-SPF22B-BB

TECHNICAL CARD



Ceiling spotlight luminaire











VIDEX for 6xGX53 lamp with backlight VL-SPF22B-

INDEX: VL-SPF22B-BB







40 000 h





Ra ≥ 80





Photometric parameters

Energy consumption in on-mode of the light source (kWh/1000h) 9

Useful luminous flux of the contained light source (Фuse)	830 Lm (backlight)
Correlated color temperature	2700K (back light)
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	40000 h
Useful luminous flux of the light source reference	in a sphere (360°)

WARRANTY 2 YEARS

General parameters

Light source or containing product	Containing product
Light source replaceable	end user

Type of light source

Dimmable	no
Technology	LED
Energy efficiency class of the contained light source	F

Electrical parameters

On-mode power (Pon)	9 W (back light)
Rated voltage, frequency	AC 220-240 V, 50/60 Hz, AC 185-240 V, 50/60 Hz (back light)
Input interface	Terminal block
Electric shock protection class	I
Displacement factor (cos φ1)	0.5

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy, Ceramics

Dimensions

EAN	4820246487108
In the package	1 pc.
Outer box	5 pcs.



VIDEX for 6xGX53 lamp with backlight VL-SPF22B-BB

INDEX: VL-SPF22B-BB

Height	50 mm, 35 mm
Width	85 mm, 350 mm
Depth	85 mm, 170 mm
Unit nett weight	1.3kg

Signs marking goods

Packaging marking


CE, Utilization











We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX for 6xGX53 lamp with backlight VL-SPF22B-BB

INDEX: VL-SPF22B-BB



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025