

INDEX: VL-SPF22B-W

TECHNICAL CARD



Ceiling spotlight luminaire















WARRANTY 2 YEARS

General parameters

Light source replaceable	end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	I

Additional information

Place of installation	Ceiling
Place of application	indoor
Housing colour	White
Impact protection	IK07
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy

Dimensions

EAN	4820246484787

VIDEX for 8xGX53 lamp VL-SPF22B-W

INDEX: VL-SPF22B-W

Height	45 mm, 30 mm
Depth	80 mm, 200 mm, 400 mm
Width	220 mm, 80 mm
Outer box	5 pcs.
In the package	1 pc.

Signs marking goods

Packaging	marking	CE, Utilization






VIDEX for 8xGX53 lamp VL-SPF22B-W

INDEX: VL-SPF22B-W







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.

Date: 20.09.2024