

VIDEX for GX53 lamp VL-SPF25A-W

INDEX: VL-SPF25A-W

TECHNICAL CARD



Ceiling spotlight luminaire











VIDEX for GX53 lamp VL-SPF25A-W

INDEX: VL-SPF25A-W









WARRANTY 2 YEARS

Depth	80 mm
In the package	1 pc.
Outer box	50 pcs.
Width	80 mm
Unit nett weight	150g

General parameters

Light source replaceable end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	1

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	White
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Iron alloy

Dimensions

EAN	4820246485876
Height	70 mm

Signs marking goods

Packaging marking CE, Utilization









VIDEX for GX53 lamp VL-SPF25A-W

INDEX: VL-SPF25A-W





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 31.08.2025