

INDEX: VL-SPF26A-B

TECHNICAL CARD





Ceiling spotlight luminaire



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



VIDEX for GX53 lamp VL-SPF26A-B

INDEX: VL-SPF26A-B

Depth	80 mm
In the package	1 pc.
Outer box	50 pcs.
Width	80 mm
Unit nett weight	130g

General parameters

WARRANTY 2 YEARS

IK07

Light source replaceable	end user

-25° +50°C

Free

IP20

Signs marking goods

Packaging marking

CE, Utilization

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	Ι

Additional information

Place of installation	Ceiling
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Iron alloy

Dimensions


EAN	4820246485883
Height	55 mm












VIDEX for GX53 lamp VL-SPF26A-B

INDEX: VL-SPF26A-B

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



Class of protection against dust and moisture.
Protection against solid objects larger than 12 mm; no protection against moisture

<u>%</u>

IP20