

VIDEX VL-TF20B-RGB

INDEX: VL-TF20B-RGB

TECHNICAL CARD



LED Ambient Floor Light

























WARRANTY 2 YEARS

General parameters

Light source replaceable no

Type of light source

| Dimmable | remote controller |
|------------|----------------------|
| Technology | LED |

Electrical parameters

| Rated voltage, frequency | DC 5 V |
|---------------------------------|--------|
| Rated current | 2 A |
| Input interface | USB-A |
| Electric shock protection class | III |

Photometric parameters

| Correlated color temperature | RGB + White |
|------------------------------|-------------|
| Beam angle | 360° |
| On/Off cycles | 40000 |
| Lifetime (L70B50) | 30000 h |

VIDEX VL-TF20B-RGB

INDEX: VL-TF20B-RGB

Additional information

| Place of installation | Floor |
|-----------------------------|------------------|
| Place of application | indoor |
| Housing colour | Black |
| Ultraviolet radiation | no |
| Operating temperature range | -20° +40°C |
| Mercury content | Does not contain |
| Ingress protection | IP20 |
| Housing material | ABS, PP |

Dimensions

| EAN 4820246488198 In the package 1 pc. Outer box 4 pcs. Height 1515mm Width 128 mm Depth 128 mm Unit nett weight 570g | | |
|---|------------------|---------------|
| Outer box 4 pcs. Height 1515mm Width 128 mm Depth 128 mm | EAN | 4820246488198 |
| Height 1515mm Width 128 mm Depth 128 mm | In the package | 1 pc. |
| Width 128 mm Depth 128 mm | Outer box | 4 pcs. |
| Depth 128 mm | Height | 1515mm |
| | Width | 128 mm |
| Unit nett weight 570g | Depth | 128 mm |
| | Unit nett weight | 570g |

Signs marking goods

Recycling of waste, CE, Utilization **Packaging marking**



VIDEX VL-TF20B-RGB

INDEX: VL-TF20B-RGB





VIDEX VL-TF20B-RGB

INDEX: VL-TF20B-RGB









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX VL-TF20B-RGB

INDEX: VL-TF20B-RGB



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025