

## TECHNICAL CARD



LED Batten Light




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®

## VIDEX 72W 1.2M 5000K 8000Lm Black

### INDEX: VLE-BN-72125B



### WARRANTY 3 YEARS



NEUTRAL WHITE   
5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

### General parameters

Control gear replaceable	by the producer
Light source replaceable	by the producer
Light source or containing product	Containing product

### Type of light source

Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Mains (MLS) or non-mains (NMLS) light source	MLS
Connected light source (cls)	no

Color-tunable light source	no
High luminance light source	No
Anti-glare shield	No
Technology	LED
Energy efficiency class of the contained light source	E

### Electrical parameters

On-mode power (Pon)	72 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	386 mA
Input interface	Free wire ends
Electric shock protection class	I
Displacement factor (cos φ1)	0.9
Survival factor	0.9

### Photometric parameters

Useful luminous flux of the contained light source (Φuse)	8000 Lm
Correlated color temperature	5000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.35

### INDEX: VLE-BN-72125B

<b>Chromaticity coordinates (y)</b>	0.36
<b>R9 colour rendering index value</b>	>0
<b>The lumen maintenance factor</b>	≥96%
<b>Colour consistency in MacAdam ellipses (SDCM)</b>	<6 (5000K)
<b>Flicker metric (Pst LM)</b>	≤1
<b>Stroboscopic effect metric (SVM)</b>	≤0.4
<b>CRI Min</b>	Ra 80
<b>CRI Max</b>	Ra 88

<b>Width</b>	60 mm
<b>Depth</b>	1200 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	16 pcs.
<b>Unit nett weight</b>	675g

### Signs marking goods

<b>Packaging marking</b>	Recycling of waste, CE, Utilization
--------------------------	-------------------------------------

### Additional information

<b>Place of installation</b>	Ceiling, Wall
<b>Place of application</b>	indoor
<b>Housing colour</b>	Black
<b>Minimum distance from the illuminated object</b>	0.5 m
<b>Diffuser material</b>	Plastic
<b>Ultraviolet radiation</b>	no
<b>Operating temperature range</b>	-20° +40°C
<b>Suitable for installation in normally flammable surfaces</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP20
<b>Housing material</b>	Aluminum


### Dimensions


<b>EAN</b>	4820246484589
<b>Height</b>	45 mm



**VIDEX®**

VIDEX 72W 1.2M 5000K 8000Lm Black

**INDEX: VLE-BN-72125B**

**VIDEX<sup>®</sup>****VIDEX 72W 1.2M 5000K 8000Lm Black****INDEX: VLE-BN-72125B**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.