

## TECHNICAL CARD




LED Batten Light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

## INDEX: VLE-BN-50124



## WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрально бяла / Bianco neutro.

## General parameters

Light source or containing product	Containing product
Control gear replaceable	-
Light source replaceable	by the producer

## Type of light source

Dimmable	no
Technology	LED
Energy efficiency class of the contained light source	E

## Electrical parameters

On-mode power (Pon)	50 W
Rated voltage, frequency	AC 185-265 V, 50/60 Hz

Rated current	240 mA
Input interface	Free wire ends
Electric shock protection class	I

## Photometric parameters

Useful luminous flux of the contained light source (Φuse)	6250 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	20000 h
Useful luminous flux of the light source reference	in a sphere (360°)
CRI Min	Ra 80
CRI Max	Ra 88

## Additional information

Place of installation	Ceiling, Wall
Place of application	indoor
Housing colour	Unpainted aluminum
Diffuser material	Plastic
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain


<b>Ingress protection</b>	IP20
<b>Housing material</b>	Aluminum


### Dimensions

<b>EAN</b>	5904405541012
<b>Height</b>	25 mm
<b>Depth</b>	1215 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.
<b>Width</b>	75 mm
<b>Unit nett weight</b>	530g

### Signs marking goods

<b>Packaging marking</b>	Recycling of waste, CE, Utilization
--------------------------	-------------------------------------



**INDEX: VLE-BN-50124**


We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



Minimum distance from the illuminated object



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture