

VIDEX-BATTEN-LED-50W-NW

INDEX: VLE-BN-50124

TECHNICAL CARD





LED Batten Light









VIDEX-BATTEN-LED-50W-NW

INDEX: VLE-BN-50124









Ra ≥ 80



Free

Not Dimmable







WARRANTY 3 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Control gear replaceable	-
Light source replaceable	by the producer

Type of light source

Energy class of the light source	Е
Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	50 W
Rated voltage, frequency	AC 185-265 V, 50/60 Hz
Rated current	240 mA
Input interface	Free wire ends

Electric shock protection class

Photometric parameters

Useful luminous flux of the light source (Φ use)	6250 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	20000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Ceiling, Wall
Place of application	indoor
Housing colour	Unpainted aluminum
Minimum distance from the illuminated object	0.5 m
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions




VIDEX-BATTEN-LED-50W-NW

INDEX: VLE-BN-50124

EAN	5904405541012
Height	25 mm
Depth	1215 mm
Width	75 mm
Outer box	20 pcs.
In the package	1 pc.









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.

Date: 8.09.2024