

## TECHNICAL CARD



LED BIKE LIGHT

# VIDEX®



## WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrallyno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

### General parameters

<b>Operation mode</b>	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE
<b>Light source replaceable</b>	no
<b>Battery Warranty</b>	1 year

### Type of light source

<b>Dimmable</b>	no
<b>Technology</b>	LED

### Electrical parameters

<b>On-mode power (Pon)</b>	20 W
<b>Input interface</b>	USB-C

### Photometric parameters

<b>Useful luminous flux of the contained light source (Φuse)</b>	2000 Lm
--	---------

## VIDEX VLF-BA286 2000Lm 5000K

### INDEX: VLF-BA286

<b>Correlated color temperature</b>	5000K (neutral white)
<b>Peak luminous intensity</b>	12700 cd

### Additional information

<b>Housing colour</b>	Black
<b>Fall protection</b>	2 m
<b>Operating temperature range</b>	-20° +40°C
<b>Battery voltage</b>	3.7 V
<b>Battery capacity</b>	4000 mAh
<b>Battery type</b>	Li-ion 21700, Li-ion 18650
<b>Battery indicator</b>	4 level
<b>Battery replaceable</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP68
<b>Housing material</b>	Aviation anodized aluminum

### Dimensions

<b>EAN</b>	4820246484244
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.
<b>Height</b>	111 mm
<b>Width</b>	31 mm
<b>Depth</b>	31 mm
<b>Unit nett weight</b>	66g (holder), 121g

**VIDEX<sup>®</sup>**

VIDEX VLF-BA286 2000Lm 5000K

**INDEX: VLF-BA286****Signs marking goods****Packaging marking**

CE, Utilization



**VIDEX<sup>®</sup>**

VIDEX VLF-BA286 2000Lm 5000K

**INDEX: VLF-BA286**

# VIDEX®

## VIDEX VLF-BA286 2000Lm 5000K

### INDEX: VLF-BA286



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



2m  
SHOCK  
RESISTANT

— The protection is effective in case of a fall from a height of up to 2 meters



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

Class of protection against dust and moisture.  
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter