

# VIDEX®

VIDEX-E14-C35-6W-FIL-WW

INDEX: VLE-C35F-06143


## TECHNICAL CARD



LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



## WARRANTY 3 YEARS

### WARM WHITE



3000K

Warm White / Ciepła biel / Tepla bila / Blanc chaud / Tepla biela / Warm wit / Meleg feher / Topla bela / Topla bijela / Warmweiß / Alb cald / Šiltai balta / Silti balta / Soe valge / Тепло бяла / Bianco caldo.

### General parameters

Light source or containing product Light source

### Type of light source

Energy class of the light source	E
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	MLS
High luminance light source	No
Anti-glare shield	No
Technology	LED

### Electrical parameters

On-mode power (Pon)	6 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	52 mA
Energy consumption in on-mode of the light source (kWh/1000h)	6
Displacement factor (cos φ1)	0.5
Survival factor	0.9

### Photometric parameters

Useful luminous flux (Φuse)	806 Lm
Correlated color temperature	3000K (warm white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
Lifetime	20000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.44
Chromaticity coordinates (y)	0.4
R9 colour rendering index value	>0
The lumen maintenance factor	≥94.8%
Colour consistency in MacAdam ellipses (SDCM)	<6 (3000K)
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4

**VIDEX**<sup>®</sup>

VIDEX-E14-C35-6W-FIL-WW

INDEX: VLE-C35F-06143

CRI Min	Ra 80
CRI Max	Ra 88

**Additional information**

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20

**Dimensions**


EAN	5904405540107
Height	98 mm
Width	35 mm
Depth	35 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	14g

**Signs marking goods**

Packaging marking	Recycling of waste, CE, Not suitable for use under moisture, Utilization
-------------------	--



















### INDEX: VLE-C35F-06143



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

	The product must be used indoors
	Waste recycling after the end of the product's service life
	The product meets the requirements of EU directives
	Not suitable for use under moisture
	It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
	— Rated beam angle
	— Ra > 80 - color rendering index
	— Nominal lifetime (hours)
	— Rated On/off cycles
	— Operating temperatures range
	— The product is incompatible with light regulators
	— Colour consistency in MacAdam ellipses (SDCM)
	— The flickering of the light does not exceed the permissible level
	— The product has minimal flickering, which should not cause discomfort or danger
	— The product does not contain mercury
	— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture