

VIDEX®

VIDEX-E27-A60-10W-FIL-NW

INDEX: VLE-A60F-10274

TECHNICAL CARD




LED Bulb




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®

VIDEX-E27-A60-10W-FIL-NW
INDEX: VLE-A60F-10274


WARRANTY 3 YEARS

NEUTRAL WHITE

4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product Light source

Type of light source

Energy class of the light source	E
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	MLS
High luminance light source	No
Anti-glare shield	No

Technology LED

Electrical parameters

On-mode power (Pon)	10 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	87 mA
Energy consumption in on-mode of the light source (kWh/1000h)	10
Displacement factor (cos φ1)	0.5
Survival factor	0.9

Photometric parameters

Useful luminous flux (Φuse)	1200 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
Lifetime	20000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥94.8%
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4

VIDEX®

VIDEX-E27-A60-10W-FIL-NW
INDEX: VLE-A60F-10274

CRI Min	Ra 80
----------------	-------

CRI Max	Ra 88
----------------	-------

Additional information

Place of application	indoor
-----------------------------	--------

Operating temperature range	-20° +40°C
------------------------------------	------------

Mercury content	Does not contain
------------------------	------------------

Ingress protection	IP20
---------------------------	------

Dimensions

EAN	5904405540008
------------	---------------

Height	105 mm
---------------	--------

Width	60 mm
--------------	-------

Depth	60 mm
--------------	-------

In the package	1 pc.
-----------------------	-------

Outer box	20 pcs.
------------------	---------

Unit nett weight	34g
-------------------------	-----

Signs marking goods


Packaging marking	Recycling of waste, CE, Not suitable for use under moisture, Utilization
--------------------------	--



VIDEX®

















VIDEX-E27-A60-10W-FIL-NW

INDEX: VLE-A60F-10274



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

-  The product must be used indoors
-  Waste recycling after the end of the product's service life
-  The product meets the requirements of EU directives
-  Not suitable for use under moisture
-  It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
-  — Rated beam angle
360°
-  — Ra > 80 - color rendering index
Ra = 80
-  — Nominal lifetime (hours)
20 000 h
-  — Rated On/off cycles
20 000
-  — Operating temperatures range
-20° +40°C
-  — The product is incompatible with light regulators
Not Dimmable
-  — Colour consistency in MacAdam ellipses (SDCM)
CCT 4000K
-  — The flickering of the light does not exceed the permissible level
No Flicker
-  — The product has minimal flickering, which should not cause discomfort or danger
No Flicker
-  — The product does not contain mercury
Hg Free
-  — Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture
IP20