

# VIDEX®

VIDEX-E27-ST64-6W-FIL-DIM-AMBER-WW

INDEX: VLE-ST64FAD-06272

## TECHNICAL CARD




LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®

**VIDEX-E27-ST64-6W-FIL-DIM-AMBER-WW**
**INDEX: VLE-ST64FAD-06272**


## WARRANTY 3 YEARS

**WARM WHITE**

**2200K**

Warm White / Ciepła biel / Tepla bila / Blanc chaud /  
Tepla biela / Warm wit / Meleg feher / Topla bela / Topla  
bijela / Warmweiß / Alb cald / Šiltai balta / Silti balta / Soe  
valge / Тепло бяла / Bianco caldo.

## General parameters

<b>Light source or containing product</b>	Light source
<b>Type of light source</b>	
<b>Energy class of the light source</b>	F
<b>Dimmable</b>	yes
<b>Directional (DLS) or non-directional (NDLS) light source</b>	NDLS
<b>Connected light source (cls)</b>	no
<b>Color-tunable light source</b>	no
<b>Mains (MLS) or non-mains (NMLS) light source</b>	MLS
<b>High luminance light source</b>	No
<b>Anti-glare shield</b>	No
<b>Technology</b>	LED

## Electrical parameters

<b>On-mode power (Pon)</b>	6 W
<b>Rated voltage, frequency</b>	AC 220-240 V, 50/60 Hz
<b>Rated current</b>	33 mA
<b>Energy consumption in on-mode of the light source (kWh/1000h)</b>	6
<b>Displacement factor (cos φ1)</b>	0.5
<b>Survival factor</b>	0.9

## Photometric parameters

<b>Useful luminous flux (Φuse)</b>	550 Lm
<b>Correlated color temperature</b>	2200K (warm white)
<b>Beam angle</b>	360°
<b>Color rendering index (CRI)</b>	Ra > 80
<b>Lifetime</b>	20000 h
<b>On/Off cycles</b>	20000
<b>Useful luminous flux of the light source reference</b>	in a sphere (360°)
<b>Chromaticity coordinates (x)</b>	0.497
<b>Chromaticity coordinates (y)</b>	0.411
<b>R9 colour rendering index value</b>	>0
<b>The lumen maintenance factor</b>	≥94.8%
<b>Colour consistency in MacAdam ellipses (SDCM)</b>	<6 (2200K)
<b>Flicker metric (Pst LM)</b>	≤1
<b>Stroboscopic effect metric (SVM)</b>	≤0.4

**VIDEX**<sup>®</sup>

VIDEX-E27-ST64-6W-FIL-DIM-AMBER-WW

INDEX: VLE-ST64FAD-06272

CRI Min	Ra 80
---------	-------

CRI Max	Ra 88
---------	-------

### Additional information

Place of application	indoor
----------------------	--------

Operating temperature range	-20° +40°C
-----------------------------	------------

Mercury content	Does not contain
-----------------	------------------

Ingress protection	IP20
--------------------	------

### Dimensions

EAN	5904405540046
-----	---------------

Height	146 mm
--------	--------

Width	64 mm
-------	-------

Depth	64 mm
-------	-------

In the package	1 pc.
----------------	-------

Outer box	20 pcs.
-----------	---------


Unit nett weight	44g
------------------	-----

### Signs marking goods

**Packaging marking**

Recycling of waste, CE, Not suitable for use under moisture, Utilization



**INDEX: VLE-ST64FAD-06272**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.