

VIDEX®

VIDEX-GU10-5W-NW

INDEX: VLE-MR16e-05104

TECHNICAL CARD



LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



120°



Ra ≥ 80



20 000 h

ON/OFF
20 000

-20° +40°C



Not Dimmable



Free



IP20

WARRANTY 2 YEARS

NEUTRAL WHITE



4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

Type of light source

Energy class of the light source G

Dimmable no

Electrical parameters

On-mode power (Pon) 5 W

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Rated current 44 mA

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 420 Lm

Correlated color temperature 4000K (neutral white)

Beam angle 120°

Color rendering index (CRI) Ra > 80

VIDEX-GU10-5W-NW

INDEX: VLE-MR16e-05104

Lifetime 20000 h

On/Off cycles 20000

Useful luminous flux of the light source in a sphere (360°)
reference

Additional information

Place of application indoor

Operating temperature range -20° +40°C

Mercury content Does not contain

Ingress protection IP20

Dimensions

EAN 5904405540497

Height 55 mm

Width 50 mm


Depth 50 mm

Outer box 20 pcs.

VIDEX®

VIDEX-GU10-5W-NW

INDEX: VLE-MR16e-05104



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

