

## TECHNICAL CARD



LED Bulb



# VIDEX<sup>®</sup>



120°



Ra ≥ 80



20 000



20 000 h



Not Dimmable



-20° +40°C



Free



IP20

## WARRANTY 2 YEARS

### NEUTRAL WHITE



### 4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

### Type of light source

<b>Energy class of the light source</b>	F
---	---

<b>Dimmable</b>	no
-----------------	----

### Electrical parameters

<b>On-mode power (Pon)</b>	7 W
----------------------------	-----

<b>Rated voltage, frequency</b>	AC 220-240 V, 50/60 Hz
---------------------------------	------------------------

<b>Rated current</b>	60 mA
----------------------	-------

### Photometric parameters

<b>Useful luminous flux of the contained light source (Φ<sub>use</sub>)</b>	600 Lm
---	--------

<b>Correlated color temperature</b>	4000K (neutral white)
-------------------------------------	-----------------------

<b>Beam angle</b>	120°
-------------------	------

## VIDEX-GU10-7W-NW

### INDEX: VLE-MR16e-07104

<b>Color rendering index (CRI)</b>	Ra > 80
<b>On/Off cycles</b>	20000
<b>Lifetime (L70B50)</b>	20000 h
<b>Useful luminous flux of the light source reference</b>	in a sphere (360°)

### Additional information

<b>Place of application</b>	indoor
<b>Operating temperature range</b>	-20° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP20


### Dimensions

<b>EAN</b>	5904405540527
<b>Outer box</b>	20 pcs.
<b>Height</b>	55 mm
<b>Width</b>	50 mm
<b>Depth</b>	50 mm

# VIDEX®

## VIDEX-GU10-7W-NW

### INDEX: VLE-MR16e-07104



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product must be used indoors



120°

— Rated beam angle



Ra ≥ 80

— Ra > 80 - color rendering index



20 000

— Rated On/off cycles



20 000 h

— Nominal lifetime (hours)



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP20

— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 24.06.2026