

VIDEX®

VIDEX-E14-C35-6W-FIL-FLAME-AMBER-WW

INDEX: VLE-C35FtA-06142

TECHNICAL CARD



LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



360°



Ra ≥ 80



20 000



20 000 h



Not Dimmable



-20° +40°C



No Flicker



No Flicker



CCT 2200K



Free



IP20

WARRANTY 3 YEARS

WARM WHITE



2200K

Warm White / Ciepła biel / Tepla bila / Blanc chaud / Tepla biela / Warm wit / Meleg feher / Topla bela / Topla bijela / Warmweiß / Alb cald / Šiltai balta / Silti balta / Soe valge / Тепло бяла / Bianco caldo.

Type of light source

Energy class of the light source	E
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
High luminance light source	No
Mains (MLS) or non-mains (NMLS) light source	MLS
Anti-glare shield	No
Technology	LED

Electrical parameters

On-mode power (Pon)	6 W
---------------------	-----

VIDEX-E14-C35-6W-FIL-FLAME-AMBER-WW

INDEX: VLE-C35FtA-06142

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	52 mA
Displacement factor (cos φ1)	0.5
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	6

Photometric parameters

Useful luminous flux (Φuse)	680 Lm
Correlated color temperature	2200K (warm white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	20000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.503
Chromaticity coordinates (y)	0.411
R9 colour rendering index value	>0
The lumen maintenance factor	≥94.8%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (2200K)
CRI Min	Ra 80
CRI Max	Ra 88

VIDEX®

VIDEX-E14-C35-6W-FIL-FLAME-AMBER-WW

INDEX: VLE-C35FtA-06142

Additional information

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20

Dimensions

EAN	5904405540145
In the package	1 pc.
Outer box	20 pcs.
Height	120 mm
Width	35 mm
Depth	35 mm
Unit nett weight	15g

Signs marking goods

Packaging marking


Recycling of waste, CE, Not suitable for use under moisture, Utilization



VIDEX®

VIDEX-E14-C35-6W-FIL-FLAME-AMBER-WW

INDEX: VLE-C35FtA-06142



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

	The product must be used indoors
	Waste recycling after the end of the product's service life
	The product meets the requirements of EU directives
	Not suitable for use under moisture
	It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
	— Rated beam angle
	— Ra > 80 – color rendering index
	— Rated On/off cycles
	— Nominal lifetime (hours)
	— The product is incompatible with light regulators
	— Operating temperatures range
	— The flickering of the light does not exceed the permissible level
	— The product has minimal flickering, which should not cause discomfort or danger
	— Colour consistency in MacAdam ellipses (SDCM)
	— The product does not contain mercury
	— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture