


TECHNICAL CARD



LED Bulkhead Light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



WARRANTY 2 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product	Containing product
Light source replaceable	by the producer

Type of light source

Dimmable	no
Technology	LED
Energy efficiency class of the contained light source	F

Electrical parameters

On-mode power (Pon)	15 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	120 mA

VIDEX-BULKHEAD-LED-DANA-15W-NW

INDEX: VLE-BH120-155

Input interface	Terminal block
Electric shock protection class	II

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	1550 Lm
Correlated color temperature	5000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	25000 h
Useful luminous flux of the light source reference	in a sphere (360°)
CRI Min	Ra 80
CRI Max	Ra 88

Additional information

Place of installation	Ceiling, Flat surface, Wall
Place of application	indoor, outdoor
Impact protection	IK07
Housing colour	Gray
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain

Ingress protection	IP65
---------------------------	------

Housing material	Plastic
-------------------------	---------

Dimensions

EAN	5904405540954
------------	---------------

Height	215 mm
---------------	--------

Depth	59 mm
--------------	-------

In the package	1 pc.
-----------------------	-------

Outer box	24 pcs.
------------------	---------

Width	125 mm
--------------	--------



Signs marking goods

Packaging marking

Recycling of
waste, CE,
Utilization



INDEX: VLE-BH120-155



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



The product must be used outdoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Minimum distance from the illuminated object
0,5 m



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle
120°



Ra > 80 - color rendering index



Rated On/off cycles
ON/OFF 20 000



The product withstands a medium impact (e.g., from a blunt object)
IK07



Nominal lifetime (hours)
25 000 h



The product does not emit ultraviolet light
Free



The product is incompatible with light regulators
Not Dimmable



Operating temperatures range
-20° ~ +40°C



The product does not contain mercury
Free



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions
IP65

Date: 12.09.2025