

INDEX: VLE-BHFR-155

TECHNICAL CARD



LED Bulkhead Light











VIDEX-BULKHEAD-LED-LENA-15W-NW

INDEX: VLE-BHFR-155















Free



Not Dimmable











IP65

WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	1550 Lm
Correlated color temperature	5000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	25000 h
Useful luminous flux of the light source reference	in a sphere (360°)

General parameters

Light source or containing product	Containing product
Light source replaceable	by the producer

Light source replaceable	by the producer
Type of light source	

Dimmable no

Energy efficiency class of the contained light source

Additional information

Place of installation	Ceiling, Flat surface, Wall
Place of application	indoor, outdoor
Impact protection	IK07
Housing colour	White
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Plastic

Electrical parameters

15 W
AC 220-240 V, 50/60 Hz
130 mA
Terminal block





INDEX: VLE-BHFR-155

Dimensions

EAN	5904405540923
Outer box	24 pcs.
Height	190 mm
Width	190 mm
Depth	42 mm











190 mm

190 mm

VIDEX-BULKHEAD-LED-LENA-15W-NW

INDEX: VLE-BHFR-155

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



The product must be used outdoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Minimum distance from the illuminated object



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Integrated terminal

block

Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions





Date: 18.11.2025