

INDEX: VLE-BHFS-155

TECHNICAL CARD





LED Bulkhead Light


















INDEX: VLE-BHFS-155

120°







20 000 IK07





Free

Not Dimmable

ble Free

IF

WARRANTY 2 YEARS

NEUTRAL WHITE 5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

General parameters

by the producer

Type of light source

Energy class of the light source	F
Dimmable	no

Electrical parameters

On-mode power (Pon)	15 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	130 mA
Input interface	Terminal block
Electric shock protection class	ll

Photometric parameters

Useful luminous flux of the light source (Φ use)	1600 Lm
Correlated color temperature	5000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	25000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Ceiling, Flat surface, Wall
Place of application	indoor, outdoor
Housing colour	White
Impact protection	IK07
Minimum distance from the illuminated object	0.5 m
Diffuser material	PC
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Plastic

Dimensions

EAN 5904405540930



INDEX: VLE-BHFS-155

Height	190 mm
Width	190 mm
Depth	42 mm
Outer box	24 pcs.

Signs marking goods

Packaging	marking	
Packaging	marking	

Recycling of waste, CE, Utilization








INDEX: VLE-BHFS-155





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.

Date: 8.09.2024