

INDEX: VLE-BHFS-155B

TECHNICAL CARD



LED Bulkhead Light

















VIDEX-BULKHEAD-LED-VIKA-BLACK-15W-NW

INDEX: VLE-BHFS-155B















25 000 h












| ree | Not Dimmable | -20° +40°C | No Flicker | No F |
|------|--------------|-------------|------------|------|
| ⊃∠6v | 11/4 | ∧ ^∘ | | |



+ <6x ellipse MacAdam





CCT 5000K Free IP65

WARRANTY 2 YEARS





Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

Electrical parameters

| On-mode power (Pon) | 15 W |
|---------------------------------------------------------------|---------------------------|
| Rated voltage, frequency | AC 220-240 V, 50/60 Hz |
| Rated current | 130 mA |
| Input interface | Terminal block |
| Electric shock protection class | II |
| Displacement factor (cos φ1) | 0.7 |
| Survival factor | 1 |
| Energy consumption in on-mode of the light source (kWh/1000h) | 15 |

General parameters

| Light source or containing product | Containing product |
|------------------------------------|--------------------|
| Light source replaceable | by the producer |

Photometric parameters

| Useful luminous flux of the contained light source (Фuse) | 1550 Lm |
|-----------------------------------------------------------|-----------------------------|
| Correlated color temperature | 5000K (neutral white) |
| Beam angle | 120° |
| Color rendering index (CRI) | Ra > 80 |
| On/Off cycles | 20000 |
| Lifetime (L70B50) | 25000 h |
| Useful luminous flux of the light source reference | in a sphere (360°) |
| Chromaticity coordinates (x) | 0.35 |
| Chromaticity coordinates (y) | 0.36 |

Type of light source

| Dimmable | no |
|----------------------------------------------------------|------|
| Directional (DLS) or non-directional (NDLS) light source | NDLS |
| Connected light source (cls) | no |
| Color-tunable light source | no |
| Mains (MLS) or non-mains (NMLS) light source | MLS |
| High luminance light source | No |
| | |



VIDEX-BULKHEAD-LED-VIKA-BLACK-15W-NW

190 mm

INDEX: VLE-BHFS-155B

Height

| R9 colour rendering index value | >0 |
|-----------------------------------------------|------------|
| The lumen maintenance factor | ≥95.8% |
| Flicker metric (Pst LM) | ≤1 |
| Stroboscopic effect metric (SVM) | ≤0.4 |
| Colour consistency in MacAdam ellipses (SDCM) | <6 (5000K) |
| CRI Min | Ra 80 |
| CRI Max | Ra 88 |

| Outer box | 24 pcs. |
|------------------|---------|
| Width | 190 mm |
| Depth | 42 mm |
| Unit nett weight | 360g |

Signs marking goods

| | Recycling of |
|-------------------|--------------|
| Packaging marking | waste, CE, |
| | Utilization |

Additional information

| Place of installation | Ceiling, Flat surface, Wall |
|----------------------------------------------------------|--------------------------------|
| Place of application | indoor, outdoor |
| Impact protection | IK07 |
| Housing colour | Black |
| Diffuser material | Polycarbonate (PC) |
| Minimum distance from the illuminated object | 0.5 m |
| Ultraviolet radiation | no |
| Operating temperature range | -20° +40°C |
| Suitable for installation in normally flammable surfaces | yes |
| Mercury content | Does not contain |
| Ingress protection | IP65 |
| Housing material | Plastic |



Dimensions

| EAN | 5904405542576 |
|----------------|---------------|
| In the package | 1 pc. |






INDEX: VLE-BHFS-155B











We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX-BULKHEAD-LED-VIKA-BLACK-15W-NW

INDEX: VLE-BHFS-155B



The product must be used indoors



The product must be used outdoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Minimum distance from the illuminated object



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The flickering of the light does not exceed the permissible level



The product has minimal flickering, which should not cause discomfort or danger



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 18.11.2025