


## TECHNICAL CARD



LED Bulkhead Light with motion detector

**INDEX: VLE-BHR-115W-SP**

**WARRANTY 2 YEARS**
**NEUTRAL WHITE**


Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

**General parameters**

<b>Light source or containing product</b>	Containing product
<b>Light source replaceable</b>	by the producer

**Type of light source**

<b>Dimmable</b>	no
<b>Technology</b>	LED
<b>Energy efficiency class of the contained light source</b>	F

**Electrical parameters**

<b>On-mode power (Pon)</b>	11 W
<b>Rated voltage, frequency</b>	AC 220-240 V, 50/60 Hz
<b>Rated current</b>	95 mA

<b>Input interface</b>	Free wire ends
<b>Electric shock protection class</b>	II

**Photometric parameters**

<b>Useful luminous flux of the contained light source (Φuse)</b>	1200 Lm
<b>Correlated color temperature</b>	5000K (neutral white)
<b>Beam angle</b>	120°
<b>Color rendering index (CRI)</b>	Ra > 80
<b>On/Off cycles</b>	20000
<b>Lifetime (L70B50)</b>	25000 h
<b>Useful luminous flux of the light source reference</b>	in a sphere (360°)
<b>Sensor light threshold</b>	25 Lx
<b>CRI Min</b>	Ra 80
<b>CRI Max</b>	Ra 88

**Additional information**

<b>Place of installation</b>	Ceiling, Flat surface, Wall
<b>Place of application</b>	indoor, outdoor
<b>Impact protection</b>	IK07
<b>Housing colour</b>	White
<b>Minimum distance from the illuminated object</b>	0.5 m
<b>Diffuser material</b>	Polycarbonate (PC)
<b>Ultraviolet radiation</b>	no
<b>Motion sensor</b>	yes

**INDEX: VLE-BHR-115W-SP**

<b>Sensor type</b>	PIR
<b>Sensor detection angle</b>	120°
<b>Sensor time delay</b>	60 s
<b>Sensor detection distance</b>	≤6 m
<b>Operating temperature range</b>	-20° +35°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP54
<b>Housing material</b>	Plastic



**Dimensions**

<b>EAN</b>	5904405540978
<b>Height</b>	170 mm
<b>Depth</b>	50 mm
<b>Width</b>	170 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.

**Signs marking goods**

<b>Packaging marking</b>	Recycling of waste, CE, Utilization
--------------------------	-------------------------------------



**INDEX: VLE-BHR-115W-SP**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product must be used indoors



The product must be used outdoors



Minimum distance from the illuminated object



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing