

VIDEX-CLS-NATA-48W-NW

INDEX: VLE-CLS-484M

TECHNICAL CARD



LED Ceiling Fixture







VIDEX-CLS-NATA-48W-NW

INDEX: VLE-CLS-484M



120°









Ra ≥ 80

25 000 h

Free

Not Dimmable







WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

Type of light source

Dimmable Energy efficiency class of the contained	no

Electrical parameters

On-mode power (Pon)	48 W
Rated voltage, frequency	AC 176-264 V, 50/60 Hz
Rated current	230 mA

Input interface	Terminal block
Electric shock protection class	1

Photometric parameters

Useful luminous flux of the contained light source (Фuse)	5160 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	25000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Ceiling, Wall
Place of application	indoor
Housing colour	White
Diffuser material	PMMA
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP44
Housing material	Plastic

Dimensions

EAN 5904405540619



VIDEX-CLS-NATA-48W-NW

INDEX: VLE-CLS-484M

Outer box	5 pcs.
Height	480 mm
Width	480 mm
Depth	70 mm











480 MM

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX-CLS-NATA-48W-NW

INDEX: VLE-CLS-484M



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



— Rated beam angle



- Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



- The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid foreign objects with a diameter of 1 mm and greater and against water splashes

Date: 18.11.2025