

# VIDEX®

VIDEX-LED-EDGE-RC-RGB-72W-WHITE

INDEX: VLE-ERC-RGB-72W

## TECHNICAL CARD




### LED DIMMABLE PENDANT LUMINAIRE WITH REMOTE CONTROL



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX<sup>®</sup>



## WARRANTY 3 YEARS

### General parameters

Control gear replaceable	by the producer
Light source replaceable	by the producer
Light source or containing product	Containing product

### Type of light source

Energy class of the light source	F
Dimmable	remote controller
Directional (DLS) or non-directional (NDLS) light source	NDLS
Mains (MLS) or non-mains (NMLS) light source	MLS
Connected light source (cls)	no
Color-tunable light source	yes
High luminance light source	No
Anti-glare shield	No
Technology	LED

## VIDEX-LED-EDGE-RC-RGB-72W-WHITE

### INDEX: VLE-ERC-RGB-72W

### Electrical parameters

On-mode power (Pon)	72 W
Rated voltage, frequency	AC 175-265 V, 50/60 Hz
Rated current	350 mA
Input interface	Free wire ends
Electric shock protection class	I
Displacement factor (cos φ1)	0.9
Survival factor	1
Standby Power (Psb)	0.4 W

### Photometric parameters

Useful luminous flux of the light source (Φuse)	7500 Lm
Correlated color temperature	6000K (cold white), 2700K (warm white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	35000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.384
Chromaticity coordinates (y)	0.378
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%

## INDEX: VLE-ERC-RGB-72W

Colour consistency in MacAdam ellipses (SDCM)	<6 (2700K), <6 (6000K)
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
CRI Min	Ra 80
CRI Max	Ra 88

Outer box	5 pcs.
Unit nett weight	1.65kg

## Signs marking goods

### Packaging marking


Recycling of  
waste, CE,  
Utilization


## Additional information

Place of installation	Ceiling, Wall
Place of application	indoor
Housing colour	White
Minimum distance from the illuminated object	0.5 m
Diffuser material	Polycarbonate (PC)
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum alloy

## Dimensions

EAN	5904405542224
Height	80 mm
Width	450 mm
Depth	450 mm
In the package	1 pc.



**VIDEX<sup>®</sup>****VIDEX-LED-EDGE-RC-RGB-72W-WHITE****INDEX: VLE-ERC-RGB-72W**

**INDEX: VLE-ERC-RGB-72W**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

