

## TECHNICAL CARD



LED Ceiling Fixture



# VIDEX®



## WARRANTY 2 YEARS

NEUTRAL WHITE

4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

Control gear replaceable	by the producer
Light source replaceable	by the producer

## Type of light source

Energy class of the light source	F
Dimmable	no

## Electrical parameters

On-mode power (Pon)	48 W
Rated voltage, frequency	AC 176-264 V, 50/60 Hz
Rated current	230 mA
Input interface	Terminal block
Electric shock protection class	I

## VIDEX-TOMA-48W-NW

### INDEX: VLE-CLR-484S

## Photometric parameters

Useful luminous flux of the light source (Φuse)	5160 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	25000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)

## Additional information


Place of installation	Ceiling, Wall
Place of application	indoor
Housing colour	White
Diffuser material	PMMA
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP44
Housing material	Plastic


## Dimensions

EAN	5904405540596
Height	480 mm
Width	480 mm

**VIDEX**<sup>®</sup>

VIDEX-TOMA-48W-NW

**INDEX: VLE-CLR-484S****Depth** 70 mm**Outer box** 5 pcs.

**INDEX: VLE-CLR-484S**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.