

INDEX: VL-DL5R-22CW

TECHNICAL CARD





LED Ceiling Light with decorative backlight

















INDEX: VL-DL5R-22CW











30 000 h Free

Not Dimmable











CCT 5000K

no







WARRANTY 2 YEARS

General parameters	
Light source or containing product	Light source

Type of light source

Light source replaceable

F
no
NDLS
no
yes
t MLS
No
No
LED

Electrical parameters

On-mode power (Pon)	22 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	136 mA
Input interface	Terminal block
Electric shock protection class	II
Displacement factor (cos φ1)	0.7
Survival factor	1
Energy consumption in on-mode of the light source (kWh/1000h)	22

Photometric parameters

Useful luminous flux (Φuse) 2400 Lm		
Correlated color temperature	5000K (neutral white), 4000K (neutral white), 3000K (warm white)	
Beam angle	140°	
Color rendering index (CRI)	Ra > 80	
On/Off cycles	20000	
Lifetime (L70B50)	30000 h	
Useful luminous flux of the light source reference	in a sphere (360°)	
R9 colour rendering index value	>0	
The lumen maintenance factor	≥96%	
Flicker metric (Pst LM)	≤1	
Stroboscopic effect metric (SVM)	-	



INDEX: VL-DL5R-22CW

Colour consistency in MacAdam ellipses (SDCM)	<6 (3000K), <6 (4000K), <6 (5000K)
CRI Min	Ra 80
CRI Max	Ra 88

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization

Additional information

Place of installation	Ceiling
Place of application	indoor, outdoor
Housing colour	White
Diffuser material	Polypropylene (PP)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP54
Housing material	ABS

	VIDEX.	
	22V Channel Streeters Streeters	
	13000	
	CEILING LIGHT #22-07	
	LIGHT	
WARRANTY 2 YEARS	220-240 Y-50/50 Hz	
7 2 n	2400#	

Dimensions

EAN	4820246487351
In the package	1 pc.
Outer box	20 pcs.
Height	293 mm
Width	293 mm
Depth	26 mm
Unit nett weight	580g





INDEX: VL-DL5R-22CW














INDEX: VL-DL5R-22CW









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



INDEX: VL-DL5R-22CW



The product must be used indoors



The product must be used outdoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Minimum distance from the illuminated object



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The flickering of the light does not exceed the permissible level



Colour consistency in MacAdam ellipses (SDCM)



Colour consistency in MacAdam ellipses (SDCM)



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing

Date: 18.11.2025