

INDEX: VLE-TF11W

TECHNICAL CARD



LED Dimmable Desk Lamp







INDEX: VLE-TF11W











Free









Lifetime	30000 h
On/Off cycles	25000
Useful luminous flux of the light source reference	in a sphere (360°)

WARRANTY 2 YEARS

General parameters

Type of light source

Dimmable	non-step
	dimming

Electrical parameters

Rated voltage, frequency	DC 5 V
Rated current	1 A
Input interface	USB-C
Electric shock protection class	III

Photometric parameters

Luminous flux	100 Lm
Correlated color temperature	5500K (cold white), 4000K (neutral white), 3000K (warm white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80

Additional information

Place of installation	Desk
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-10° +40°C
Battery type	Li-ion
Battery capacity	1800 mAh
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic

Dimensions

EAN	5904405541210
Width	74 mm
Height	264 mm
Depth	74 mm
Outer box	20 pcs.



INDEX: VLE-TF11W












INDEX: VLE-TF11W



Short touch - change the light color temperature Long touch - smooth dimming Fold the lamp and double touch - turn on the bottom torch







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,

VIDEX-DESK-LAMP-BERLIN

INDEX: VLE-TF11W

30-732 Krakow, Poland.



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Rated beam angle



Ra > 80 - color rendering index



Nominal lifetime (hours)



Rated On/off cycles



The product does not emit ultraviolet light



The product has smooth brightness adjustment



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 25.03.2025